

ITEM CODE	POWER	COL. TEMP	PF	DIMENSION	CUT OUT	CRI	BEAM ANGLE
-----------	-------	-----------	----	-----------	---------	-----	------------



SKYLITE - 12W Slim LED Down Light - Round

GL91302WW	12W	3000K	>0.9	∅118x33	∅106	>85	115°
GL91302NW	12W	4000K	>0.9	∅118x33	∅106	>85	115°
GL91302CD	12W	6000K	>0.9	∅118x33	∅106	>85	115°



SKYLITE - 18W Slim LED Down Light - Round

GL91304WW	18W	3000K	>0.9	∅168x33	∅156	>85	115°
GL91304NW	18W	4000K	>0.9	∅168x33	∅156	>85	115°
GL91304CD	18W	6000K	>0.9	∅168x33	∅156	>85	115°



SKYLITE - 24W Slim LED Down Light - Round

GL91305WW	24W	3000K	>0.9	∅220x33	∅208	>85	115°
GL91305NW	24W	4000K	>0.9	∅220x33	∅208	>85	115°
GL91305CD	24W	6000K	>0.9	∅220x33	∅208	>85	115°



SKYLITE - 12W Slim LED Down Light - Square

GL92302WW	12W	3000K	>0.9	118x118x33	106x106	>85	115°
GL92302NW	12W	4000K	>0.9	118x118x33	106x106	>85	115°
GL92302CD	12W	6000K	>0.9	118x118x33	106x106	>85	115°



SKYLITE - 18W Slim LED Down Light - Square

GL92304WW	18W	3000K	>0.9	168x168x33	156x156	>85	115°
GL92304NW	18W	4000K	>0.9	168x168x33	156x156	>85	115°
GL92304CD	18W	6000K	>0.9	168x168x33	156x156	>85	115°

All dimensions are in mm

ITEM CODE	POWER	COL. TEMP	PF	DIMENSION	CUT OUT	CRI	BEAM ANGLE
-----------	-------	-----------	----	-----------	---------	-----	------------

SKYLITE - 24W Slim LED Down Light - Square

GL92305WW	24W	3000K	>0.9	220x220x33	208x208	>85	115°
GL92305NW	24W	4000K	>0.9	220x220x33	208x208	>85	115°
GL92305CD	24W	6000K	>0.9	220x220x33	208x208	>85	115°



SKYLITE
LED DOWN LIGHT



All dimensions are in mm



IS 15685/Part 2/Sec13:2012



50%
Energy saving
over CFLs



Zero
Maintenance



4 times
more life
over CFLs



Zero
Mercury

